



Section 01 – Accommodation Modules - Sales

Item 01020515

**Available up to 50 x 4 Man Ex Rental Offshore
Accommodation modules for Sale.**

A60 Accommodation CSC Certified

**Excellent Condition – Manufactured between 2008 and
2011 for Rental Fleet.**



DETAIL AS FOLLOWS:

Hazardous Area Classification

Not classified but can be upgraded to become Zone 2 at additional cost.

Certification Body

Det Norsk Veritas for Frame. Lloyds for CSC.

Conforms with the Convention of Safe Container (CSC) and can be shipped by standard shipping lines.

Weight

6,5000Kg

Framework Design Temperature

-20 °C to +50 °C

HVAC

2 x 18,000 BTU Split Units. Internal Design Temp 24 °C

Detection & Alarm System

Connection to main Rig/Vessel Alarm System is included.

<u>Ter No.</u>	<u>Colour</u>	<u>Description</u>
1 & 2	Red, Black	Smoke Detection
3 & 4	Red, Black	Manual Call Point



5 & 6	Red, Black	Beacon Red (24 V DC)
7 & 8	Blue, White	Beacon Blue (24 V DC)
9 & 10	Orange, Green	Alarm Bell (24 V DC)
11 & 12	Spare	
3 & 14	Blue, Blue/White	Telephone
5 & 16	Spare	
7 & 18	Red, Black	PA Speaker (100 V, 3W 120Hz)

Fire Rating

A60 SOLAS

Certification Regulations

Offshore Service Container DNV 2.7-1 or BS 12079.

Stacking Capability

192,000 Kg

Payload

5,250 Kg

Size

20' Standard CSC Container (L 6058 x W 2438 x H 2591mm).

Slings

4 wire type, rated Max Gross Mass of 33,000 Kg.

Electrical Connection



Suitable for operation on single or 2 phase systems at 220Vac 50/60Hz.
Rated at 12KVA. Container is supplied with 30m of power cable.
Earthing is required at supply cable and to the chassis via the earth boss.

Connection Details

Potable Water	1" BSP Threaded male copper Black
Water	4" ANSI 150# Flange, RF-CS Grey Water 2" ANSI 150# Flange, RF-CS
Power	3Cx10mm ² flame retardant, braided cable 0.6/1KV grade, IEC 332-3, IEC 92-375
Fire & Gas	6 Pair 1.5mm ² Fire resistant braided 250V cables. IEC 332-3, IEC 92-350
Telephone	2 pair 0.75mm ² Fire resistant braided 250V grade cables. IEC 332-3, IEC 92-375
PA Speaker	2Cx1.5mm ² Fire resistant, braided 250V grade cables. IEC 332-3, IEC 92-375

PHOTOGRAPHS:









NOTES:

- Purchase for one or multiple units acceptable.
- All Units Fully Certified.
- All items offered subject to prior sale.
- Price each dependant on Quantity, Age etc.
- Located 'as is, where is' GCC – Middle East.
- We are advised by Owners that the Units are in excellent condition, and the manufacture of the units were between 2008 and 2011.
- Assistance can be offered by Owners with any Export or relocation concerns.
- Full Manufacturers Documentation Packages are available upon request subject to formal request for Inspection.
- Inspection arranged by prior appointment.