

## Section 07 – Gas Compressors - Sales Item 07080512

(PPE Ref: GS 23-1349)

## 2000Hp 2000 Rpm Acid Gas Injection Compressor c/w 4060v/3ph/60Hz Electric Motor – Brand New.

## **DETAIL AS FOLLOWS:**

- Ariel JGK/6 Throw, Six Stage.
- Design Capacity 115 10<sup>3</sup>SM<sup>3</sup>/d (42% H2S) from 48 KPag Suction to 10 MPag Discharge.
- Hyundai 2000HP, 2000RPM, 4060v/3ph/60Hz Electric Motor (WP2 Enclosure).
- Voith Hydraulic Speed Reducer (type EL 11 Y.1 torque convertor)
- Output Range 400 1200RPM.
- Air-X-Changers model 132-2Z acid gas cooler with six cooling sections and two 30HP fans.
- Air-X-Changers model 84BH section hydraulic oil cooler with one 15HP fan.
- Kilowatts Guardian control panel, Stainless steel vessels, piping and components between cooler sections and following stage cylinder inlets.
- 7620mm x 12192 mm flat top skid with integral waste oil tanks.
- Breaks down to 4369mm shipping width by removing outriggers.



**Equip. Status:** Surplus Year Built: 2010 **Service Type:** Sour Equip. Cond.: Const. Skidded: Y Const. Housed: **NPITS** Υ Const. Pkg'd: **Driver Type:** Comp. Mfg.: Electric Ariel

Comp. Model #: JGK/6 Driver Mfg.: Hyundai Driver Model #: HNP7.563-6

Driver Size: 2000BHP Panel Make + Model: Guardian PLC # of Stages: 6

1st St. Suction Bottle A#:		600606	CRN#:		V233.2		S/N:	08-551-511	
1st St. Discharge Bottle A#:		600599	CRN#:	V2319.2		S/N:		08-551-521	
2nd St. Suction Bottle A#:		600587	CRN#:		V2337.2		S/N:	08-551-522	
2nd St. Discharge Bottle A#:		600595	CRN#:		V2339.2		S/N:	08-551-522	
3rd St. Suction Bottle A#:		600550	CRN#:		V2312.2	S/N:		08-551-513	
3rd St. Discharç Bottle A#:	ge	600596	CRN#:		V2306.2		S/N:	08-551-532	
Cyl. 1st St. ID	22in		@ MAWP	285psi	285psig				
Cyl. 1st St. ID #2:	15 7/8in		@ MAWP	635psig					
Cyl. 3rd St. ID	10.5in		@ MAWP	845psig					
Cly. 3rd St. ID #2:	5 1/4in		@ MAWP	2435psig					
Cooler Mfg.: Cooler Serial #:	Aerial 80663.6		Cooler Model:	Air X Changer Type Z		Cooler 1st CRN U9838.2			

Cyl. 4th Stage: ID 5 ¼" @ MAWP 2435 psi, Cyl. 5th Stage: ID 5 "@ MAWP 2515 psi Cyl. 6th Stage: ID 3.5 "@ MAWP 4501 psi 4th St. Suction A#: 600588 CRN #: V2313.2 S/N: 08-551-514 4th St. Discharge A#: 600593 CRN #: V2310.2 S/N: 08-551-524 5th St. Suction A#: 600590 CRN #: V2343.2 S/N: 08-551-515 5th St. Discharge A#: 600594 CRN #: V2311.2 S/N: 08-551-525 6th St. Suction A#: 600591 CRN #: V2344.2 S/N: 08-551-5166th St Discharge A#: 600598 CRN #: V2321.2 S/N: 08-551-526 • Building and crane to fit compressor skid offered separately. Crane members incorporate integral lube oil day tanks. Design: up to 4.3 mmcfd of acid gas (approx. 40% H2S and 60% CO2) from a suction pressure of 7 to 10 psig to a discharge



pressure of 1450 psig. Designed to operate between 400 RPM to 1200 RPM recycle c/w Voith adjustable torque converter Type EL13.1, coupled between motor and compressor



## Notes:

- Available subject to prior sale.
- Located in Canada.
- Full Documentation Packages are available upon request.